XPM - % Paramagnetic Oxygen Analyzer

Base Analyzer			
Paramagnetic Oxygen Analyzer	XPM601		
Configuration			
Exd Certified - ATEX, UKEX, IECEx, cQPSus		EX	
Calibrated Range			
Measurement range: 05%		В	
Background Gas			
Background gas: Hydrogen		G	
SIL Capability			
No SIL capability			А
SIL 2 capable - meets the requirements of IEC61508			В

Ordering example

XPM601-EX-BGA	Hazardous area Paramagnetic O2 analyzer Certified: ATEX / UKEX / IECEx / cQPSus Measurement range 05.% Background Gas: Hydrogen Standard features include: HMI (backlit LCD & 4 buttons), 2 x 420mA outputs, MODBUS RTU (RS485), 2 x concentration alarms and IP66 rated wall mount enclosure Requires 24Vdc
---------------	--

Gas fitting adapters	
GEN-2PK-FIT-A	1/8" NPT to 1/8" Swagelok Tube Adaptor
GEN-2PK-FIT-B	1/8" NPT to 1/4" Swagelok Tube Adaptor
GEN-2PK-FIT-C	1/8" NPT to 6mm Swagelok Tube Adaptor
GUB accessories	
GEN-BLANKPLUG	Blanking Plug
XTP601-M20CONDUIT	M20 Conduit Entry 3/4" NPT (Nickel Plated Brass)
XTP601-M20BARRIER	M20 Cable Gland (Nickel Plated Brass 20S - Barrier)
XPM601 Operational Spares	
GEN-26149	Fuse for main PCB
GEN-14198	GUB Lid o-ring
XPM601 Additonal Documentation	n
* GEN-DOC	Certificate of Origin from the Chamber of Commerce
* EXPORT-DOC	Certificate of Conformity
XPM601 Extended Warranty	
* XPM601-EW24	Extended warranty 24 months from invoice date
* XPM601-EW36	Extended warranty 36 months from invoice date
* On certain labor intensive services,	no discount can be offered. These items are always offered at list price.

Please note: Michell Instruments adopts a continuous development program which sometimes necessitates specification changes without notice. Please contact us for latest version. Issue No: XPM601 Order Codes_V1