

## XTP601

### Thermo-Paramagnetic Oxygen Analyzer

Fixed Configurations	
Nitrogen (N2) Applications	
<b>XTP601-EX1-C1-N2</b>	SIL2 Capable Hazardous Area certified O2 in N2 analyzer: Range: 0...25% O2 with Viton O-ring, 60°C Cell and flame arrestors. Supplied with Material certificates Equivalent Code - XTP601+EX1+C1+D6+E1+F3+L1+M1
<b>XTP601-EX1-C2-N2</b>	SIL2 Capable Hazardous Area certified O2 in N2 analyzer: Range: 0...25% O2 with Silicone O-ring, 60°C Cell and flame arrestors. Supplied with Material certificates Equivalent Code - XTP601+EX1+C2+D6+E1+F3+L1+M1
<b>XTP601-EX1-C3-N2</b>	SIL2 Capable Hazardous Area certified O2 in N2 analyzer: Range: 0...25% O2 with Ekraz O-ring, 60°C Cell and flame arrestors. Supplied with Material certificates Equivalent Code - XTP601+EX1+C3+D6+E1+F3+L1+M1

### Configurable Product

Product Ordering Code {Feature A}+{Feature C}+...+{Feature F}+{Feature M}		
Feature	Item	Description
<b>Feature {A}</b>	<b>Base Model</b>	
	XTP601	Thermo-paramagnetic oxygen analyzer. Standard features include: HMI (backlit LCD & 4 buttons), IP66 rated wall mounted enclosure, 316 stainless steel sample path, 2 x 4-20mA outputs, MODBUS RTU (RS485), 2 x concentration alarms and 24Vdc powered.
<b>Feature {B}</b>	<b>Case &amp; Area Class</b>	
	GP1	General Purpose Analyzer (1/4" NPT(F) gas connections)
	GP2	General Purpose Analyzer with flame arrestors (1/8" NPT(F) gas connections)
	EX1	Explosion-proof Analyzer for use in hazardous areas with flame arrestors (1/8" NPT(F) gas connections)
<b>Feature {C}</b>	<b>Cell O-Ring Material</b>	
	C1	Viton
	C1E	Viton (for enriched oxygen ranges ie O2 >21%)
	C2	Silicone - NOT for use with enriched O2 (ie O2 > 21%)
	C3	Ekraz Sensor Cell O-ring
	C3E	Ekraz (for enriched oxygen ranges ie O2 >21%)
<b>Feature {D}</b>	<b>Range - verify selection using Sensor Matrix</b>	
	D1	Range 0 to 1% Oxygen
	D2	Range 0 to 2% Oxygen
	D3	Range 0 to 5% Oxygen
	D4	Range 0 to 10% Oxygen
	D5	Range 0 to 21% Oxygen
	D6	Range 0 to 25% Oxygen (calibrated 0 to 21%)
	D7	Range 0 to 50% Oxygen
	D8	Range 80 to 100% Oxygen
	D9	Range 90 to 100% Oxygen
	D11	Range 0 to 4% Oxygen
	D12	Range 0 to 0.5% Oxygen
	D13	Range 20 to 100% Oxygen
	** D1A	Range 0 to 1% Oxygen
	** D2A	Range 0 to 2% Oxygen
	** D3A	Range 0 to 5% Oxygen
	** D4A	Range 0 to 10% Oxygen
	** D5A	Range 0 to 21% Oxygen
	** D6A	Range 0 to 25% Oxygen
<b>Feature {E}</b>	<b>Background Gas - verify selection using Sensor Matrix</b>	
	E1	Nitrogen (N2)
	E2	Carbon Dioxide (CO2)
	E3	Methane (CH4)
	E4	Hydrogen (H2)
	E5	BIOGAS (60%CH4/40%CO2) - unless otherwise stated
	E6	Natural Gas - C8 Mixture
	E7	Argon (Ar)
	E8	Helium (He)
	Es	Special Gas
<b>Feature {F}</b>	<b>Cell temperature</b>	
	F1	Cell temp 50°C
	F3	Cell temp 60°C
<b>Feature {L}</b>	<b>SIL</b>	
	L0	Standard product
	L1	Meets the requirements of IEC61508 (SIL 2 Capable)
<b>Feature {M}</b>	<b>Material Certification</b>	
	M0	No material certification
	* M1	Material certificate to BS EN 10204 - type 3.1
<b>Feature {X}</b>	<b>Individual Build Options</b>	
	X3	CFOS - Cleaned for O2 service (standard with O2 ranges >25%)
	X9	Product Review Required
<b>* On certain labor intensive services, no discount can be offered. These items are always offered at list price.</b>		
<b>** Analyzer calibrated as Air Ingress</b>		
<b>NOTE: For other gas combinations and measurement ranges please contact O2 Support Group</b>		

**XTP601 Approved Range / Gas Combinations**

		E1	E2	E3	E4	E5	E6	E7	E8
	Oxygen	N2	CO2	CH4	H2	CH4/CO2	C8	Ar	He
D12	0 to 0.5%								
D1	0 to 1%								
D2	0 to 2%								
D11	0 to 4%								
D3	0 to 5%				Note 1				
D4	0 to 10%								
D5	0 to 21%								
D6	0 to 25%								
D7	0 to 50%								
D13	20 to 100%								
D8	80 to 100%								
D9	90 to 100%								
D1A	0 to 1%								
D2A	0 to 2%								
D3A	0 to 5%				Note 1				
D4A	0 to 10%								
D5A	0 to 21%			Note 2		Note 2	Note 2		
D6A	0 to 25%			Note 2		Note 2	Note 2		

**Note 1** Calibration points up to 4%

**Note 2** Calibration points in flammable region performed in N2

Good  
NOT Allowed  
Flammable gas

**XTP601 Additional Options**

Item Number	Description
<b>Calibration</b>	
XTP-ATP	Additional Test Point - Contact O2 Support Group for Pricing
<b>Warranty</b>	
* XTP601-EW24	Extended warranty 24 months from invoice date
* XTP601-EW36	Extended warranty 36 months from invoice date
<b>Documentation</b>	
* EXPORT-DOCS	Certificate of Origin from the Chamber of Commerce
* GEN-DOC	Certificate of Conformity
* GEN-DOC-B	0

**XTP601 Spares and Accessories**

<b>GUB accessories</b>	
XTP601-BLANKPLUG	Blanking Plug
XTP601-M20CONDUIT	M20 Conduit Entry 3/4" NPT (Nickel Plated Brass)
XTP601-M20COMPRESS	M20 Cable Gland (Nickel Plated Brass 20S - Compression) (GP1 only)
XTP601-M20BARRIER	M20 Cable Gland (Nickel Plated Brass 20S - Barrier)
XTP601-14198	GUB Lid o-ring
<b>Gas fitting adaptors - for GP1 (1/4" NPTF)</b>	
XTP601-6MM	1/4" NPT to 6mm Swagelok Tube Adaptor
XTP601-1/4"	1/4" NPT to 1/4" Swagelok Tube Adaptor
GEN-20114C	1/4" NPT to 1/8" Swagelok Tube Adaptor
<b>Gas fitting adaptors - for GP2 &amp; EX1 (1/8" NPTF)</b>	
GEN-2PK-FIT-A	1/8" NPT to 1/8" Swagelok Tube Adaptor
GEN-2PK-FIT-B	1/8" NPT to 1/4" Swagelok Tube Adaptor
GEN-2PK-FIT-C	1/8" NPT to 6mm Swagelok Tube Adaptor
<b>Display</b>	
XTP601-GP-HMI	Display assembly for GP model
XTP601-EX-HMI	Display assembly for EX model
<b>Miscellaneous</b>	
XTP601-26149	Fuse for main PCB
XTP601-TFUSE	Thermal Fuse (70°C)
XTP601-RC	Ribbon cable assembly
PTFE-TAPE-02	Unsintered PTFE tape for use with enriched oxygen samples
<b>* On certain labor intensive services, no discount can be offered. These items are always offered at list price.</b>	

# XTP501

## Thermo-Paramagnetic Oxygen Analyzer

Fixed Configurations	
Nitrogen (N2) Applications	
XTP501-1-N2-25	General Purpose wall mounted thermoparamagnetic oxygen analyzer, ranged 0...25% O2 in N2. Configured with HMI and supplied with Power, Output and Alarm cables. No Material certificates supplied Equivalent Code - XTP501+GP1+C3+E1+F2+M0
XTP501-1-N2-80	General Purpose wall mounted thermoparamagnetic oxygen analyzer ranged 80...100% O2 in N2. Configured with HMI and supplied with Power, Output and Alarm cables. Cleaned for O2 Service. No Material certificates supplied Equivalent Code - XTP501+GP1+C5+E1+F2+M0+X3
XTP501-2-N2-25	General Purpose wall mounted thermoparamagnetic oxygen analyzer ranged 0...25% O2 in N2. Configured as Transmitter and supplied with Power, Output and Alarm cables. No Material certificates supplied Equivalent Code - XTP501+GP2+C3+E1+F2+M0

### Configurable Product

Feature	Item	Description
<b>Product Ordering Code {Feature A}+{Feature C}+{Feature D}+...+{Feature F}+{Feature X}</b>		
Feature	Item	Description
<b>Feature {A}</b>	<b>Base Model</b>	
	XTP501	General Purpose wall mounted thermoparamagnetic oxygen analyzer. Standard features include: 316 stainless steel sample path, 2 x 4-20mA outputs, MODBUS RTU (RS485), 2 x Concentration alarms, 24V DC powered and housed in an IP55 rated enclosure.
<b>Feature {B}</b>	<b>Case &amp; Area Class</b>	
	GP1	Analyzer with HMI (backlit LCD & 4 buttons)
	GP2	Transmitter with Status LED
<b>Feature {C}</b>	<b>Range - verify selection using Sensor Matrix</b>	
	C1	Range 0 to 1% Oxygen
	C2	Range 0 to 5% Oxygen
	C3	Range 0 to 25% Oxygen
	C4	Range 20 to 100% Oxygen
	C5	Range 80 to 100% Oxygen
	C7	Range 0 to 50% Oxygen
<b>Feature {E}</b>	<b>Background Gas - verify selection using Sensor Matrix</b>	
	E1	Nitrogen (N2)
	E2	Carbon Dioxide (CO2)
	E4	Hydrogen (H2)
	E7	Argon (Ar)
	E8	Helium (He)
<b>Feature {F}</b>	<b>Cables</b>	
	F0	Loose connectors
	F1	Power & Output (5m) and loose connector
	F2	Power, Output & Alarm (5m) and loose connector
	F3	Power, Output, Alarm and Input (5m)
<b>Feature {M}</b>	<b>Material Certification</b>	
	M0	No material certification
	* M1	Material certificate to BS EN 10204 – type 3.1
<b>Feature {X}</b>	<b>Individual Build Options</b>	
	X3	CFOS - Cleaned for O2 service (standard with O2 ranges >25%)
	X9	Product Review Required
<b>* On certain labor intensive services, no discount can be offered. These items are always offered at list price.</b>		

**XTP501 Approved Range / Gas Combinations**

		E1	E2	E4	E7	E8
	Oxygen	N2	CO2	H2	Ar	He
C1	0 to 1%					
C2	0 to 5%			<i>Note 1</i>		
C3	0 to 25%					
C7	0 to 50%					
C4	20 to 100%					
C5	80 to 100%					

**Note 1** Calibration points up to 4%

- Good
- NOT Allowed
- Flammable gas

**XTP501 Additional Options**

Item Number	Description
<b>Calibration</b>	
XTP-ATP	Additional Test Point - Contact O2 Support Group for Pricing
<b>Warranty</b>	
* XTP501-EW24	Extended warranty 24 months from invoice date
* XTP501-EW36	Extended warranty 36 months from invoice date
<b>Documentation</b>	
* EXPORT-DOCS	Certificate of Origin from the Chamber of Commerce
* GEN-DOC	Certificate of Conformity
* GEN-DOC-B	0

**XTP501 Spares and Accessories**

<b>Cables and connectors</b>	
XTX501-HMI-IC-0.5	0.5m interconnect cable
XTX501-HMI-IC-01	1m interconnect cable
XTX501-HMI-IC-02	2m interconnect cable
XTX501-MCA	Mating Connector-alarms
XTX501-MCP	Mating Connector-power
XTX501-MCS	Mating Connector-signal output
XTX501-MCSI	Mating Connector-signal input
XTX501-MCA-05	Connector:Alarms with 5m cable fitted
XTX501-MCS-05	Connector:Signals out with 5m cable fitted
XTX501-MCSI-05	Connector:Signals in with 5m cable fitted
XTX501-MCP-05	Connector:Power with 5m cable fitted
XTX501-TC	Tamperproof cover for power interrupt switch
<b>Display</b>	
XTX501-HMI-RD	Remote Display 501series for Transmitter configuration (GP2)
<b>* On certain labor intensive services, no discount can be offered. These items are always offered at list price.</b>	

**Please note: Michell Instruments adopts a continuous development program which sometimes necessitates specification changes without notice. Please contact us for latest version. Issue No: XTP Series Order Codes\_97314\_V15\_UK\_0723**